4.070,649

4,128,829

4,184,147

1/1978

1/1980

12/1978

[45] Apr. 14, 1981

[54]	PROCESSI	ING OF INFORMATION
[75]	Inventors:	Derek Buckle; Timothy D. Strand, both of Dorset, England
[73]	Assignee:	Quest Automation Limited, Dorset, England
[21]	Appl. No.:	43,596
[22]	Filed:	May 29, 1979
[30]		n Application Priority Data
May 31, 1978 [GB] United Kingdom 25935/78		
FE 17	T-+ (7.1	G06K 9/22
[51]	THE CITY	340/146.3 SY; 178/18
[52]	U.S. Ci	179/19 10.
[58]	Field of Se	arch
	340/146	3.3 SY, 146.3 SG, 146.3 AC, 146.3 MA
[56]		References Cited
U.S. PATENT DOCUMENTS		
3.4	87,371 12/19	969 Frank 340/146.3 H
-,-	75,331 4/19	975 Hasenbalg 178/18
3,909,785 9/19		75 Howells 340/146.3 SY
4,005,400 1/19		977 Engdahl 178/18
4,0	18,989 4/19	77 Snyder et al 178/18
4,0	35,768 7/19	
		*** 1. T 1 140/146 2 SV

Wright, Jr. et al. ...... 340/146.3 SY

Herbst et al. ..... 340/146.3 SY

Seelbach ...... 340/146.3 SY

Primary Examiner—Leo H. Boudreau Attorney, Agent, or Firm—Pollock, Vande Sande & Priddy

## [57] ABSTRACT

A handwriting recognition device comprises a transducer surface responsive to a pen positioned thereon for representing the coordinate position of the pen as an electrical signal, and data processing means for recognizing a handwriting effected with the pen, the data processing means including a microprocessor based control controlling a read/write memory, a non-volatile read-only memory storing a handwriting recognition routine to store recognized handwriting in the read/write memory, and an interface communicating to a host computer system a representation of the recognized character. A visual display may be provided coupled to a display interface and an input information for receiving verified recognized handwriting communicated from the host computer system. The read/write memory has a first storage location coupled to the transducer storing a representation of signals from the transducer, a second storage location coupled to the interface and storing a representation of recognized handwriting, and a third storage location coupled to the display interface and storing an image of the display.

9 Claims, 15 Drawing Figures

